

ALUMINUM STOREFRONT HARDWARE



LH8016



8710S (GROOVED)



LH191BB



OR

LH5016



OR

LH199BB





ALUMINUM STOREFRONT HARDWARE

LH191BB

- ▶ Certification: ANSI/BHMA A156.1 and A156.7
- ▶ Description: Standard Weight 5 Knuckle 2 ball bearing hinges Stainless Steel
- ▶ Sizes:

Inches	mm	Inches	mm
4-1/2" x 4"	(114X102)	.134	(3.4)
4-1/2" x 4-1/2"	(114X114)	.134	(3.4)
5" x 4"	(127X102)	.146	(3.7)
5" x 4-1/2"	(127X114)	.146	(3.7)
5" x 5"	(127X127)	.146	(3.7)
- ▶ Finishes: US32D
- ▶ Options NRP/ETW/PIC/RC/HT cUL Listing stamp for fire

LH199BB

- ▶ Certification: ANSI/BHMA A156.1 and A156.7
- ▶ Description: Heavy Weight 5 Knuckle 4 ball bearing hinges Stainless Steel
- ▶ Sizes:

Inches	mm	Inches	mm
4-1/2" x 4"	(114X102)	.180	(4.6)
4-1/2" x 4-1/2"	(114X114)	.180	(4.6)
5" x 4"	(127X102)	.190	(4.6)
5" x 4-1/2"	(127X114)	.190	(4.6)
5" x 5"	(127X127)	.190	(4.6)
- ▶ Finishes: US32D
- ▶ Options NRP/ETW/PIC/RC/HT cUL Listing stamp for fire

LH5016

- ▶ Heavy Duty Closer • Ideally suited for commercial use • Cast aluminum body • Adjustable Size 1 - 6 • Size 1 meets ADA requirement • Tri-packed (regular, top jamb, and parallel arm mount) • UL/cUL listed • BHMA Certified ANSI A156.4 Grade 1 to 2,000,000 cycles • Three valves regulate closing, latching speed and back check. • Finishes: Aluminum (AL), Bronze (DU), Black (BLK) • Optional Plastic Cover

LH8016

- ▶ Extra Heavy Duty Cast Iron Closer • Suitable for educational, healthcare, main entrances and other high traffic application where maximum control of the door is required. • Adjustable Size 1 - 6 • Size 1 meets ADA requirement • Tri-packed (regular, top jamb, and parallel arm mount) • Track arm, hold open, cushion and stop, hold cushion, spring cushion, spring hold cushion and stop and heavy duty arm. • Other options include long rod and shoe. • Drop plates • UL/cUL listed • BHMA Certified ANSI A156.4 Grade 1 to 2,000,000 cycles • 4 valves regulate closing, latching speed back check • and (Delayed Action) • Finishes: Aluminum (AL), Bronze (DU), Black (BLK) • Complete with plastic cover.

8710S (GROOVED)

- ▶ Narrow Rim Exit Devices The Lawrence Hardware 8500/8700 series has a full line of heavy duty wide stile Panic and Fire Rated Exit hardware. This series is the perfect choice for safety, security, durability and modern appearance. They are designed for use on contemporary glass aluminum doors.
- ▶ Device Widths Short (3') and Long (4')
- ▶ Minimum Stile Width 2-19/32" (66mm)
- ▶ Latch Bolt 3/4" (19mm) throw, deadlocking design
- ▶ Dogging Options Cylinder Dogging (CD)
- ▶ Mounting Height Standard device centreline from finished floor is 40" (1016mm)
- ▶ Projection Push bar Neutral 3-1/16" (78mm).
- ▶ Push bar Depressed 2-19/32" (66mm)