



LH303

- Medium Duty Closer
- Ideally suited for suite entry doors and light commercial
- Cast aluminum body
- Tri-packed (regular, top jamb ,and parallel arm mount)
- Two valves regulate closing and latching speed
- Finishes: Aluminum (AL), Bronze (DU), Brass (PB)
- Warranty - 5 years

Certification:

- UL 10C listed - Positive pressure fire tests of door assemblies
- Approved to be used for ANSI/NFPA 80 fire rated opening up to & including 3 hr.
- CAN/ULC-S133 listed - Door Closers intended for use with Swinging Doors
- Conforms to BHMA / ANSI A156.4 Grade 2

Footprint H:1-5/8" (41mm)
W: 7-1/8" (181mm)
Projection: 2-3/8" (60mm)

See template for the hole dimensions



LH503BC/LH534BC

- Medium Duty Closer
- Ideally suited for commercial use
- Cast aluminum body
- Back check - Standard
- Size 3 (503) and size 4 (534) available
- Tri-packed (regular, top jamb, and parallel arm mount)
- Two valves regulate closing and latching speed
- Finishes: Aluminum (AL), Bronze (DU), Brass (PB).
- Warranty - 5 years

Certification:

- UL 10C listed - Positive pressure fire tests of door assemblies
- Approved to be used for ANSI/NFPA 80 fire rated opening up to & including 3 hr.
- CAN/ULC-S133 listed - Door Closer intended for use with Swinging Doors
- Conforms to BHMA / ANSI A156.4 Grade 2

Footprint H:1-5/8" (41mm)
W: 8-7/8" (225mm)
Projection: 2-7/8" (73mm)

See template for the hole dimensions