

**LH8016BCDA**

- Heavy Duty Closer
- Suitable for educational, healthcare, main entrances and other high traffic application where maximum control of the door is required
- Adjustable Size 1 - 6
- DA (Delayed Action) and BC (Back check) - Standard
- Four valves regulate closing, latching speed, delayed action & back check
- Tri-packed (regular, top jamb and parallel arm mount)
- Track arm, hold open and cushion stop available
- Non-handed
- Finishes: Aluminum (AL), Bronze (DU), Black (BLK)
- Plastic cover - Standard
- Optional Steel cover finishes include C32D and C26.
- Warranty - 20 years

Certification:

- UL 10C listed - Positive pressure fire tests of door assemblies
- CAN/ULC-S133 listed - Door Closers intended for use with Swinging Doors
- BHMA Certified ANSI A156.4 Grade 1 to 1,500,000 cycles
- Approved to be used for ANSI/NFPA 80 fire rated opening up-to & including 3 hr
- Size 1 conforms to ADA requirement

Note: Hold open feature is not suited for fire rated door application

CAUTION: Door Closers for Low Opening Force Applications:

Door closers installed in openings required to meet the requirements of the Americans With Disabilities Act or ANSI/BHMA Standard A117.1, when adjusted to meet those requirements, may not provide adequate closing power to dependably close and latch the door.

Footprint H: 3-1/2" (89mm)

W: 12-1/4" (311mm)

Projection: 2-1/4" (57mm)

See template for the hole dimensions