

NARROW STILE DEVICE LENGTH 8500/8700 SERIES

The Device lengths are precut for 36" (914mm) and 48" (1219mm) wide door use (standard shipping size).

THE SHORT DEVICE, 36"

(914mm) has an actual end to end length of 34 1/4" (870mm) suitable for a 36" (914mm) wide door use.

Push pad length is 18 1/4" (546mm)

The short Device can be cut down to a minimum end to end size of:

Standard Device (S) 27 (686mm)

Fire Rated Device (F) 25 1/4" (641mm)

THE LONG DEVICE, 48"

(1219mm) has an actual end to end length of 45" (1143mm) suitable for a 48" (1219mm) wide door use. Push pad length is 21-1/2" (456mm)

The long device can be cut down to a minimum end to end size of:

Standard Device (S) 32-1/2" (826mm)

Fire Rated Device (F) 31 (787mm)

VERTICAL RODS

Our standard and fire rated vertical rod exit device accommodates up to 8' (2438mm) doors. Fire rated devices may be ordered for up to 10' (3048mm) fire exit doors. Specify door height if greater than standard sizes when ordering.

Note: For fire rated devices consult door manufactures literature for maximum allowable door height & width.

End to end length does not include latch bolt.

Sex Nuts and Bolts (SNB)

SNB-For 1-3/4" Door

618



1-9/16"

3/4"

SNB-For 2-1/4" Door

623



1-9/16"

1"

SNB-For 2-1/2" Door

630



1-9/16"

1-1/4"