100

EXIT DEVICES

LAWRENCEHARDWARE.COM

8000 Series

Heavy Duty

Grade 1

The 8000 Series is a heavy duty modern push bar design that offers two external surface styles: smooth device body (optional) and grooved device body (standard). The 8500 and 8600 Series feature a smooth device body. The 8700 and 8800 Series are grooved device bodies.

These two styles feature rugged performance and elegant appearance. The two styles are uniform in dimensions and mechanical construction. The two different styles provide a choice for architects and end users.

8500 SERIES (NARROW STILE)

Smooth device body (Non Stock)



8600 SERIES (WIDE STILE)

Smooth device body (Non Stock)



1-800-267-1236 Please note that product specs subject to change. SECTION 3A



LAWRENCEHARDWARE.COM 8000 Series Heavy Duty Grade 1

CERTIFICATION

UL/cUL Listed: Listing for Panic Exit Hardware and 3 Hour rating for Fire Exit Hardware ANSI/BHMA Certified: Devices are A156.3 Grade 1.

APPLICATIONS

8610S (smooth)/8810S (grooved) Rim Exit Devices are used for all types of single and double door applications with mullion.

8610F (smooth)/8810F (grooved) Fire Rated Rim Exit Devices are used for listed fire labeled single doors up to 4' x 10' (1219mm x 3048mm) or 8' x 10' (2438mm x 3048mm) double doors with mullion.

FINISHES

Lawrence Hardware Exit Devices are available in the following architectural finishes: US3, US4, US10, US10B, US19, US26, US26D and US32D.

SPECIFICATIONS

Device Lengths Short (36") actual end to end length 33-1/2" (850mm)

Long (48") actual end to end length 45-1/2" (1137mm)

Door Widths Short (36") for 29" to 36" (736mm to 914mm) door size

Long (48') for 33" to 48" (838mm to 1219mm) door size

Minimum Stile Width 4-1/4" (107mm)

Latch Bolt 3/4" (19mm) throw, deadlocking design

Strikes 801 (Panic), 802 (Fire)

Dogging Panic Device - Hex Key Dogging (RD) standard

Fire Exit device - No Dogging (ND)

Dogging Options Cylinder Dogging (CD)

Less Dogging (LD)

Fasteners Panic Device - Machine screws furnished standard for HMD.

For wood doors sex nuts and bolts (SNB) can be ordered separately

Fire Exit Device - Sex nuts and bolts (SNB) supplied standard

Mounting Height Standard device centreline from finished floor is 40" (1016mm)

Projection Push bar Neutral 3-1/16" (78mm). Push bar Depressed 2-19/32" (66mm)





801 802

1-800-267-1236 Please note that product specs subject to change. SECTION 3A