

EXIT DEVICES

Surface Vertical Rod Exit Devices (SVR)

The Lawrence Hardware 8600/8800 series has a full line of heavy duty wide stile Panic and Fire Rated Exit hardware. This series is the perfect choice for safety, security, durability and modern appearance.



8630S (SMOOTH)/8830S (GROOVED)

Panic Rated SVR Exit Devices



8630F (SMOOTH)/8830F (GROOVED)

Fire Rated SVR Exit Devices

EXIT DEVICES

LAWRENCEHARDWARE.COM

8000 Series

Heavy Duty

Grade 1

107

CERTIFICATION

UL/cUL Listed: Listing for Panic Exit Hardware and 3 Hour rating for Fire Exit Hardware
ANSI/BHMA Certified: Devices are A156.3 Grade 1.

APPLICATIONS

8630S (smooth)/8830S (grooved) SVR Exit Devices are used primarily for double door applications
8630F (smooth)/8830F (grooved) Fire Rated SVR Exit Devices are used for listed fire labeled double doors up to 8' x 10' (2438mm x 3048mm)

FINISHES

Lawrence Hardware Exit Devices are available in the following architectural finishes: US3, US4, US10, US10B, US19, US26, US26D and US32D.

SPECIFICATIONS

Device Lengths	Short (36") actual end to end length 33-1/2" (850mm) Long (48") actual end to end length 45-1/2" (1137mm)
Door Widths	Short (36") for 29" to 36" (736mm to 914mm) door size Long (48") for 33" to 48" (838mm to 1219mm) door size
Minimum Stile Width	4-1/4" (107mm)
Latch Bolt	Top latch - 5/8" (16mm) throw. Bottom latch - 5/8" (16mm) throw. Held in retracted position during door swing
Strikes	Top - 812 (panic), 822 (fire) Bottom - 815 (panic), 825 (fire)
Dogging	Panic Device - Hex Key Dogging (RD) standard Fire Exit device - No Dogging (ND)
Dogging Options	Cylinder Dogging (CD) Less Dogging (LD)
Fasteners	Panic Device - Machine screws furnished standard for HMD For wood doors sex nuts and bolts (SNB) can be ordered separately Fire Exit Device - Sex nuts and bolts (SNB) supplied standard
Mounting Height	Standard device centreline from finished floor is 40" (1016mm)
Door Opening Height	Available for Standard door height of 7' or 8'
Vertical Rods	1/2" (13mm) diameter tubular with rod guides. Top rod has two pieces for accommodating 7' or 8' doors Bottom rod is one piece with a length of 31-1/4" (794mm)
Projection	Push bar Neutral 3-1/16" (78mm). Push bar Depressed 2-19/32" (66mm)



812



822



815



825