





Model 88L and 88E Series Escutcheon Levers (Flat Top & Bottom Escutcheon)

FEATURES

1. Non-handed trim is easy to install
2. Easy operating lever handle allows for convenient one hand operation
3. Most popular 8 finishes to choose from: US3 (605), US4 (606), US10 (612), US10B (613), US19 (622), US26 (625), US26D (626), US28 (689), and US32D (630).
4. Escutcheon Trim has 4 through bolts connected to the device chassis for more security and durability.
5. Trims fit 1-3/4" (44mm) doors standard. For 2" (51mm), 2-1/4" (57mm) or any other non standard door thickness please specify door thickness when ordering.
6. 88L and 88E Escutcheons and levers are alloy cast.
7. Anti-Vandalism design prevents lock from damage. When key locks the lever is rigid and in the horizontal position.
8. Cylinder sold separately

MODELS AND FUNCTIONS

Operation Options	Key Locks and Unlocks Lever	Lever Always Active (no Cylinder)	Key Retracts Latchbolt (Rigid Lever)	Pull When Device Dogged (Rigid Lever)
(Dummy trim is not recommended for fire rated devices)*				
Function	Classroom	Passage	Storeroom	Dummy*
Trim Designation	Cylinder Escutcheon Lever	Blank Escutcheon Lever	Night Latch Escutcheon Lever	Dummy Escutcheon Lever
Model number and uses	For Rim, Surface / Concealed Vertical Rod and LBR			
	88L01A	88L01B	88L01C	88L01D
	For Mortise Lock Exit Devices Only			
	88E01A	88E01B	88E01C	88E01D
Escutcheon Plate Size	9-7/16" x 2-15/16" x 13/16" (240mm x 75mm x 21mm)			
ANSI Function Number	8	14	3	2
Cylinder Type	Mortise	Not required	Rim	Not required

Note: Standard 01 Lever shown