

Hinges Full Mortise Hinges - Standard Weight

Full mortise hinge for use on medium weight doors that have medium to high frequency service. They are suitable for hollow metal or wood doors.



LH1379CB

Base Material:	Steel			
Hinge Bearing Type:	Concealed Bearing			
Description:	Standard Weight Concealed bearing 3 knuckle hinges Steel			
Sizes:	Inches	mm	Inches	mm
	4-1/2" x 4"	(114X102)	.134	(3.4)
	4-1/2" x 4-1/2"	(114X114)	.134	(3.4)
	5" x 4"	(127X102)	.146	(3.7)
	5" x 4-1/2"	(127X114)	.146	(3.7)
	5" x 5"	(127X127)	.146	(3.7)
Finishes:	Available in C26, C26D, C10B, C19 (Black)			
Options:	Non removable pin (NRP), Radius Corner (RC) - 1/4" radius			
Electrical Modification:	Electric Through Wire (ETW) / Plug in Connector (PIC) - Check with factory			

Certification:

- UL10C Listed - Positive Pressure Fire Test of Door Assemblies
- CAN/ULC-S104 Listed - Standard Method for Fire Tests of Door Assemblies
- For use on swinging type doors rated up-to and including 3 hr
- Approved to be used for ANSI/NFPA 80 fire rated opening
- Conforms to ANSI/BHMA A156.1 & A156.7



LH1391CB

Base Material:	Stainless Steel			
Hinge Bearing Type:	Concealed Bearing			
Description:	Standard Weight Concealed bearing 3 knuckle hinges Stainless Steel			
Sizes:	Inches	mm	Inches	mm
	4-1/2" x 4"	(114X102)	.134	(3.4)
	4-1/2" x 4-1/2"	(114X114)	.134	(3.4)
	5" x 4"	(127X102)	.146	(3.7)
	5" x 4-1/2"	(127X114)	.146	(3.7)
	5" x 5"	(127X127)	.146	(3.7)
Finishes:	Available in C32D			
Options:	Non removable pin (NRP), Radius Corner (RC) - 1/4" radius & Hospital tip (HT)			
Electrical Modification:	Electric Through Wire (ETW) / Plug in Connector (PIC) - Check with factory			

Certification:

- UL10C Listed - Positive Pressure Fire Test of Door Assemblies
- CAN/ULC-S104 Listed - Standard Method for Fire Tests of Door Assemblies
- For use on swinging type doors rated up-to and including 3 hr
- Approved to be used for ANSI/NFPA 80 fire rated opening
- Conforms to ANSI/BHMA A156.1 & A156.7