

Hinges Full Mortise Hinges - Standard Weight

Full mortise hinge for use on medium weight doors that have medium to high frequency service. They are suitable for hollow metal or wood doors.



LH1379CB

Certification:	ANSI/BHMA A156.1 and A156.7			
Description:	Standard Weight Concealed bearing 3 knuckle hinges Steel			
Sizes:	Inches	mm	Inches	mm
	4-1/2" x 4"	(114X102)	.134	(3.4)
	4-1/2" x 4-1/2"	(114X114)	.134	(3.4)
	5" x 4"	(127X102)	.146	(3.7)
	5" x 4-1/2"	(127X114)	.146	(3.7)
	5" x 5"	(127X127)	.146	(3.7)
Finishes:	US26, US26D, US10B, C19 (Black)			
Options	NRP/ETW/PIC/RC cUL Listing stamp for fire			



LH1391CB

Certification:	ANSI/BHMA A156.1 and A156.7			
Description:	Standard Weight Concealed bearing 3 knuckle hinges Stainless Steel			
Sizes:	Inches	mm	Inches	mm
	4-1/2" x 4"	(114X102)	.134	(3.4)
	4-1/2" x 4-1/2"	(114X114)	.134	(3.4)
	5" x 4"	(127X102)	.146	(3.7)
	5" x 4-1/2"	(127X114)	.146	(3.7)
	5" x 5"	(127X127)	.146	(3.7)
Finishes:	US32D			
Options	NRP/ETW/PIC/RC/HT cUL Listing stamp for fire			