BUTT HINGES

LAWRENCEHARDWARE.COM

Full Mortise

Standard Weight

5 Knuckle 2 Ball Bearing

Hinges Full Mortise Hinges - Standard Weight

Full mortise hinge for use on medium weight doors that have medium to high frequency service. They are suitable for hollow metal or wood doors.



LH179BB

Certification: ANSI/BHMA A156.1 and A156.7

Description: Standard Weight 5 Knuckle 2 ball bearing

hinges Steel

Sizes: Inches mm Inches mm

4-1/2" x 4" (114X102) .134 (3.4) 4-1/2" x 4-1/2" (114X114) .134 (3.4) 5" x 4" (127X102) .146 (3.7) 5" x 4-1/2" (127X114) .146 (3.7)

(127X127) .146

(3.7)

Finishes: US26, US26D, US10B, C19 (Black)

Options NRP/ETW/PIC/RC

5" x 5"

cUL Listing stamp for fire



LH191BB

Certification: ANSI/BHMA A156.1 and A156.7

Description: Standard Weight 5 Knuckle 2 ball bearing

hinges Stainless Steel

Sizes: Inches mm Inches mm

4-1/2" x 4" (114X102) .134 (3.4) 4-1/2" x 4-1/2" (114X114) .134 (3.4) 5" x 4" (127X102) .146 (3.7) 5" x 4-1/2" (127X114) .146 (3.7) 5" x 5" (127X127) .146 (3.7)

Finishes: US32D

Options NRP/ETW/PIC/RC/HT

cUL Listing stamp for fire

1-800-267-1236 Please note that product specs subject to change. SECTION 1A