

## Full Mortise Hinges - Standard Weight - Economy Hinge

Full mortise hinge for use on medium weight doors that have medium frequency service. They are suitable for hollow metal or wood doors.



### LH603BB

Certification:	Conforms to A156.7			
Description:	Standard Weight 5 Knuckle 2 ball bearing hinges Steel			
Sizes:	Inches	mm	Inches	mm
	4-1/2" x 4"	(114X102)	.134	(3.4)
	4-1/2" x 4-1/2"	(114X114)	.134	(3.4)
Finishes:	US26D, C19 (Black)			
Options	NRP/RC			

## Full Mortise Hinges - Standard Weight - Spring Hinge

Fully adjustable; spring tension may be increased or decreased during installation. Apartments, hotel or motel rooms, condominiums and office buildings or anywhere self closing doors are required. Use 2 spring hinges on fire doors, centre and bottom location. All other applications: Up to 70lbs, 1 spring hinge with 2 ball bearing hinges. Spring hinge in centre. Upto 90lbs, 2 spring hinges with 1 ball bearing hinge. Spring hinge in centre and bottom. Upto 120lbs, 3 spring hinges.



### LH606SH

Certification:	ANSI/BHMA A156.17			
Description:	Standard Weight, Spring hinges Steel			
Sizes:	Inches	mm	Inches	mm
	4-1/2" x 4"	(114X102)	.134	(3.4)
	4-1/2" x 4-1/2"	(114X114)	.134	(3.4)
Finishes:	US26D, C19 (Black)			
Options	RC			